



## Surface Mount Schottky Rectifier



### Features

- Low profile package
- Ideal for automated placement
- Low power losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

### Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

### Mechanical Data

- **Package:** SOD-123FL  
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

### ■ Maximum Ratings (T<sub>j</sub>=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	S14T
Device marking code			S14T
Repetitive peak reverse voltage	VRRM	V	40
Maximum RMS Voltage	VRMS	V	28
Average rectified output current @60Hz sine wave, Resistance load, TL (FIG.1)	IO	A	1.0
Surge(non-repetitive)forward current @60Hz half-sine wave,1 cycle, T <sub>j</sub> =25°C	IFSM	A	30
Storage temperature	T <sub>stg</sub>	°C	-55 ~+150
Junction temperature	T <sub>j</sub>	°C	-55 ~+150
Typical Junction capacitance @4V,1MHz	C <sub>j</sub>	pF	55

### ■ Electrical Characteristics (T<sub>j</sub>=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	S14T
Maximum instantaneous forward voltage drop per diode	V <sub>F</sub>	V	I <sub>FM</sub> =1.0A	0.55
Maximum DC reverse current at rated DC blocking voltage per diode @ VRM=VRRM	IRR <sub>M</sub>	mA	T <sub>j</sub> =25°C	0.10
			T <sub>j</sub> =125°C	10

Note1:Pulse test:300uS pulse width,1% duty cycle

Note2:Pulse test:pulse width 40mS



# S14T

## ■ Thermal Characteristics ( $T_j=25^\circ\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	S14T
Thermal Resistance	R $\theta$ J-A	$^\circ\text{C}/\text{W}$	85
	R $\theta$ J-L		18

## ■ Characteristics (Typical)

FIG1:  $I_o$ -TL Curve




FIG2: Surge Forward Current Capability




FIG3: Forward Voltage





FIG4: Typical Reverse Characteristics






# S14T

## Ordering Information (Example)


PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S14T	F1	Approximate 0.0169	3000	30000	120000	7" reel
S14T	F2	Approximate 0.0169	2500	25000	100000	7" reel
S14T	F3	Approximate 0.0169	10000	30000	210000	13" reel
S14T	F4	Approximate 0.0169	3000	27000	108000	7" reel
S14T	F5	Approximate 0.0169	10000	20000	160000	13" reel
S14T	F6	Approximate 0.0169	3000	12000	60000	7" reel

## Outline Dimensions



SOD-123FL		
Dim	Min	Max
A	1.60	1.90
B	0.90	1.10
C	2.55	2.85
D	3.60	3.90
E	1.00	1.20
F	0.40	0.90
G	0.10	0.25
H	0.02	0.05

## Suggested pad layout



SOD-123FL	
Dim	Millimeters
P1	3.90
P2	1.90
Q1	1.00
Q2	1.50



## S14T

---

### Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.